

Jumper in thick film technology - Automotive variant

Type: ADF-Jumper


Sizes: 0402, 0603, 0805, 1206, 1210, 1218, 2010, 2512

Characteristics:

- Chip resistors in thick film technology
- Resistance area coated with glass and varnish passivation
- AEC Q200 qualified
- RoHS-conform and Halogen-free according to IEC 61249-2-21 / IPC 4101B
- Customer specific barcodes available - also in 2D
- All sizes can be manufactured with the following contact variants
⇒ Electroplated pure tin

Dimensions (in mm):

Size	L Length		W Width		H Depth		t Contact back		T Contact front	
	Min	Max	Min	Max	Min	Max	Min	Max	Min	Max
0402	0,95	1,05	0,45	0,55	0,25	0,40	0,10	0,35	0,05	0,35
0603	1,50	1,70	0,75	0,95	0,35	0,55	0,10	0,50	0,10	0,50
0805	1,85	2,15	1,10	1,40	0,35	0,65	0,15	0,60	0,15	0,60
1206	2,90	3,35	1,45	1,75	0,35	0,65	0,25	0,75	0,15	0,75
1210	3,00	3,30	2,35	2,65	0,50	0,75	0,35	0,85	0,25	0,85
1218	3,00	3,30	4,50	4,80	0,50	0,75	0,35	0,85	0,25	0,85
2010	4,80	5,20	2,30	2,70	0,50	0,75	0,35	0,85	0,25	0,85
2512	6,10	6,50	3,00	3,30	0,50	0,75	0,35	0,85	0,25	0,85



Packaging units:

Reel Ø	Card tape acc. EN 60286-3	Blister tape
180 mm	5 T pcs. 10 T pcs. for size 0402	4 T pcs.
330 mm	10 T pcs. 20 T pcs.	8 T pcs. 16 T pcs.
Samples on request		

Ordering information:

ADF		1206	0R	N	P	5 (optional)
Type	Contact	Size	R-Value	Marking	Packaging	pcs. / Reel (T pcs.)
ADF	Standard (without add.)	0402 to 2512	0R	K- with (from size 0603) N- without (only size 0402)	P- Card tape B- Blister tape S- Bulk	Depends on size and packaging unit

Jumper in thick film technology - Automotive variant

Type: ADF-Jumper

Sizes: 0402, 0603, 0805, 1206, 1210, 1218, 2010, 2512

Technical data – depending on size:

Size	Max. current I_{max} (A)	Max. R-Value R_{max} (mOhm)	Insulation voltage U_{ins} (V)		Packaging		
			1 min	Continuous	P	B	S
0402	1,50	20	75	75	x		x
0603	2,00	20	100	75	x		x
0805	2,50	20	200	75	x		x
1206	3,50	20	300	75	x		x
1210	4,00	20	300	75	x		x
1218	7,00	20	300	75		x	x
2010	5,00	20	300	75		x	x
2512	7,00	20	300	75		x	x

Technical data - general:

Technical data	
Operating temperature range	-55°C ... +155°C
Solderability acc. EN 60068-2-58	245°C 3s
Soldering heat resistance acc. EN 60068-2-58	260°C 10s

Data, unless specified, acc. EN 140401-802.