

# DC AXIAL FAN

JAMICON®

120X120X38 mm

JF1238-13 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : ±10%

## SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH <sub>2</sub> O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
JF1238B1SR	Dual Ball	12	10.2 ~ 13.8	135.8	0.356	3200	0.70	8.40	0.80	47.9	278
JF1238-1HR	B, S			118.7	0.281	2800	0.48	5.76	0.55	43.8	
JF1238-1MR				101.3	0.213	2400	0.32	3.96	0.38	39.1	
JF1238-1LR				84.5	0.155	2000	0.20	2.40	0.21	33.8	
JF1238-1ER				69.6	0.109	1700	0.10	1.20	0.11	29.6	
JF1238B2SR	Dual Ball	24	20.4 ~ 27.6	135.8	0.356	3200	0.37	8.88	0.45	47.9	
JF1238-2HR	B, S			118.7	0.281	2800	0.31	7.44	0.32	43.8	
JF1238-2MR				101.3	0.213	2400	0.22	5.28	0.23	39.1	
JF1238-2LR				84.5	0.155	2000	0.13	3.12	0.14	33.8	
JF1238-2ER				69.6	0.109	1700	0.09	2.16	0.11	29.6	
JF1238B4SR	Dual Ball	48	40.8 ~ 60.0	135.8	0.356	3200	0.20	9.60	0.22	47.9	
JF1238B4HR				118.7	0.281	2800	0.13	6.24	0.15	43.8	
JF1238B4MR				101.3	0.213	2400	0.09	4.32	0.11	39.1	
JF1238B4LR				84.5	0.155	2000	0.07	3.36	0.08	33.8	

Specifications subject to change without notice

The 7<sup>TH</sup> character of Model No means the bearing code. Please refer to the page "PART NUMBER SYSTEM". Please contact us for detail if your request bearing system is not shown in the above list.

