

# DC AXIAL FAN

JAMICON®

## 40X40X10 mm

## KF0410-01 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : ±10%

### SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH <sub>2</sub> O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Power (Watt)	Noise (dBA)	Weight (g)
KF0410B5H	Dual Ball	5	4.25~5.75	6.00	0.128	6000	0.13	0.65	0.8	28.0	16
KF0410B5M				5.38	0.106	5400	0.09	0.45	0.5	25.7	
KF0410B5L				4.12	0.066	4200	0.07	0.35	0.4	20.9	
KF0410S5H	Sleeve			6.00	0.128	6000	0.20	1.00	1.2	28.0	
KF0410S5M				5.38	0.106	5400	0.10	0.50	0.8	25.7	
KF0410S5L				4.12	0.066	4200	0.08	0.40	0.6	20.9	
KF0410B1H	Dual Ball	12	10.2~13.8	6.00	0.128	6000	0.07	0.84	0.8	28.0	
KF0410B1M				5.38	0.106	5400	0.06	0.72	0.7	25.7	
KF0410B1L				4.12	0.066	4200	0.05	0.60	0.6	20.9	
KF0410S1H	Sleeve			6.00	0.128	6000	0.08	0.96	1.2	28.0	
KF0410S1M				5.38	0.106	5400	0.07	0.84	0.8	25.7	
KF0410S1L				4.12	0.066	4200	0.06	0.72	0.7	20.9	
KF0410B2S	Dual Ball	24	20.4~27.6	6.58	0.148	6600	0.06	1.44	1.4	30.6	
KF0410B2H				6.00	0.128	6000	0.05	1.20	1.2	28.0	
KF0410B2M				5.38	0.106	5400	0.04	0.96	1.0	25.7	
KF0410B2L	Sleeve			4.12	0.066	4200	0.03	0.72	0.8	20.9	
KF0410S2H				6.00	0.128	6000	0.05	1.20	1.2	28.0	
KF0410S2M				5.38	0.106	5400	0.04	0.96	1.0	25.7	
KF0410S2L	4.12	0.066	4200	0.03	0.72	0.8	20.9				

Specifications subject to change without notice

