

DC AXIAL FAN

JAMICON®

40X40X10 mm

KF0410-03 KF0410-08 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : ±10%

SPECIFICATIONS

| Model | Bearing | Rated Voltage (V) | Operating Voltage (V) | Air Flow (CFM) | Static Pressure (inchH ₂ O) | Speed (R.P.M.) | Input Current (Amp) | Input Power (Watt) | Nominal Power (Watt) | Noise (dBA) | Weight (g) |
|-----------|-----------|-------------------|-----------------------|----------------|--|----------------|---------------------|--------------------|----------------------|-------------|------------|
| KF0410B5H | Dual Ball | 5 | 4.25~5.75 | 6.42 | 0.129 | 6000 | 0.13 | 0.65 | 0.8 | 26.4 | 16 |
| KF0410B5M | | | | 5.75 | 0.106 | 5400 | 0.09 | 0.45 | 0.5 | 24.4 | |
| KF0410B5L | | | | 4.37 | 0.067 | 4200 | 0.07 | 0.35 | 0.4 | 19.9 | |
| KF0410S5H | Sleeve | | | 6.42 | 0.129 | 6000 | 0.20 | 1.00 | 1.2 | 26.4 | |
| KF0410S5M | | | | 5.75 | 0.106 | 5400 | 0.10 | 0.50 | 0.8 | 24.4 | |
| KF0410S5L | | | | 4.37 | 0.067 | 4200 | 0.08 | 0.40 | 0.6 | 19.9 | |
| KF0410B1H | Dual Ball | 12 | 10.2~13.8 | 6.42 | 0.129 | 6000 | 0.07 | 0.84 | 0.8 | 26.4 | |
| KF0410B1M | | | | 5.75 | 0.106 | 5400 | 0.06 | 0.72 | 0.7 | 24.4 | |
| KF0410B1L | | | | 4.37 | 0.067 | 4200 | 0.05 | 0.60 | 0.6 | 19.9 | |
| KF0410S1H | Sleeve | | | 6.42 | 0.129 | 6000 | 0.08 | 0.96 | 1.2 | 26.4 | |
| KF0410S1M | | | | 5.75 | 0.106 | 5400 | 0.07 | 0.84 | 0.8 | 24.4 | |
| KF0410S1L | | | | 4.37 | 0.067 | 4200 | 0.06 | 0.72 | 0.7 | 19.9 | |
| KF0410B2S | Dual Ball | 24 | 20.4~27.6 | 6.97 | 0.159 | 6600 | 0.06 | 1.44 | 1.4 | 29.3 | |
| KF0410B2H | | | | 6.42 | 0.129 | 6000 | 0.05 | 1.20 | 1.2 | 26.4 | |
| KF0410B2M | | | | 5.75 | 0.106 | 5400 | 0.04 | 0.96 | 1.0 | 24.4 | |
| KF0410B2L | Sleeve | | | 4.37 | 0.067 | 4200 | 0.03 | 0.72 | 0.8 | 19.9 | |
| KF0410S2H | | | | 6.42 | 0.129 | 6000 | 0.05 | 1.20 | 1.2 | 26.4 | |
| KF0410S2M | | | | 5.75 | 0.106 | 5400 | 0.04 | 0.96 | 1.0 | 24.4 | |
| KF0410S2L | 4.37 | 0.067 | 4200 | 0.03 | 0.72 | 0.8 | 19.9 | | | | |

Specifications subject to change without notice

