

60X60X20 mm

KF0620-01 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : ±10%

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Power (Watt)	Noise (dBA)	Weight (g)
KF0620-1SR	B, H	12	10.2 ~ 13.8	28.27	0.289	5000	0.38	4.56	4.8	39.2	43
KF0620-1HR	B, H, S			25.36	0.233	4500	0.25	3.00	3.2	36.2	
KF0620-1M	B, H, S			22.40	0.186	4000	0.20	2.40	2.5	32.4	
KF0620-1L	B, H, S			19.45	0.142	3500	0.14	1.68	1.7	27.8	
KF0620-1E	B, H, S			16.66	0.105	3000	0.10	1.20	1.3	25.2	
KF0620-1V	B, H, S			13.82	0.072	2500	0.07	0.84	0.9	20.7	
KF0620-2SR	B, H	24	20.4 ~ 27.6	28.27	0.289	5000	0.21	5.04	5.1	39.2	
KF0620-2H	B, H, S			25.36	0.233	4500	0.14	3.36	3.5	36.2	
KF0620-2M	B, H, S			22.40	0.186	4000	0.12	2.88	3.1	32.4	
KF0620-2L	B, H, S			19.45	0.142	3500	0.10	2.40	2.5	27.8	
KF0620-2E	B, H, S			16.66	0.105	3000	0.07	1.68	1.7	25.2	
KF0620-2V	B, H, S			13.82	0.072	2500	0.04	0.96	1.2	20.7	

Specifications subject to change without notice

The 7TH character of Model No means the bearing code. Please refer to the page "PART NUMBER SYSTEM". Please contact us for detail if your request bearing system is not shown in the above list.

