

DC AXIAL FAN

JAMICON®

80X80X38 mm

KF0838-11 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : ±10%

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Current (Amp)	Noise (dBA)	Weight (g)
KF0838B1UR	Dual Ball	12	10.2 ~ 13.8	106.39	1.23	7000	1.50	18.00	2.20	60.30	188
KF0838B1SR				90.85	0.96	6100	0.98	11.76	1.20	56.40	
KF0838B1HR				75.79	0.62	5000	0.60	7.20	0.72	50.90	
KF0838B1MR				61.29	0.47	4200	0.40	4.80	0.48	46.20	
KF0838B1LR				52.55	0.34	3500	0.27	3.24	0.32	41.40	
KF0838B1ER				35.93	0.17	2500	0.14	1.68	0.17	32.30	
KF0838B1VR				28.36	0.11	2000	0.10	1.20	0.12	27.30	
KF0838B2UR	Dual Ball	24	20.4 ~ 27.6	106.39	1.23	7000	0.70	16.80	0.84	60.30	
KF0838B2SR				90.85	0.96	6100	0.52	12.48	0.62	56.40	
KF0838B2HR				75.79	0.62	5000	0.32	7.68	0.36	50.90	
KF0838B2MR				61.29	0.47	4200	0.22	5.28	0.26	46.20	
KF0838B2LR				52.55	0.34	3500	0.14	3.36	0.17	41.40	
KF0838B2ER				35.93	0.17	2500	0.08	1.92	0.10	32.30	
KF0838B2VR				28.36	0.11	2000	0.06	1.44	0.07	27.30	
KF0838B4UR	Dual Ball	48	40.8 ~ 60.0	106.39	1.23	7000	0.37	17.76	0.44	60.30	
KF0838B4SR				90.85	0.96	6100	0.24	11.52	0.29	56.40	
KF0838B4HR				75.79	0.62	5000	0.20	9.60	0.24	50.90	
KF0838B4MR				61.29	0.47	4200	0.15	7.20	0.18	46.20	
KF0838B4LR				52.55	0.34	3500	0.14	6.72	0.17	41.40	
KF0838B4ER				35.93	0.17	2500	0.10	4.80	0.12	32.30	
KF0838B4VR				28.36	0.11	2000	0.08	3.84	0.10	27.30	

Specifications subject to change without notice

