

35X35X10 mm

KF0B10-01 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : ±15%

SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH ₂ O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Power (Watt)	Noise (dBA)	Weight (g)
KF0B10-5SR	B, S	5	4.25 ~ 5.75	7.32	0.159	9500	0.23	1.15	1.2	29.9	8.5
KF0B10-5HR				6.53	0.134	8500	0.21	1.05	1.1	26.3	
KF0B10-5MR				5.78	0.113	7500	0.14	0.70	0.8	24.5	
KF0B10-5LR				4.95	0.087	6500	0.09	0.45	0.5	20.7	
KF0B10-5ER				3.66	0.055	4800	0.07	0.35	0.4	15.0	
KF0B10-1SR	12	10.2 ~ 13.8	10.2 ~ 13.8	7.32	0.159	9500	0.13	1.56	1.7	29.9	
KF0B10-1HR				6.53	0.134	8500	0.10	1.20	1.2	26.3	
KF0B10-1MR				5.78	0.113	7500	0.08	0.96	1.0	24.5	
KF0B10-1LR				4.95	0.087	6500	0.06	0.72	0.8	20.7	
KF0B10-1ER				3.66	0.055	4800	0.05	0.60	0.6	15.0	

Specifications subject to change without notice

The 7TH character of Model No means the bearing code. Please refer to the page "PART NUMBER SYSTEM".
Please contact us for detail if your request bearing system is not shown in the above list.

